



aluminium handle

Drawers colours



green blue yellow red white

ALFA 01 – PROCEDURE TROLLEY

BODY

Structure made of powder-coated steel RAL 7035, thickness 10/10, finished with acrylic polyurethane enamels resistant to scratches, stains and corrosion. Painting process complies with UNI EN ISO 9002 regulations. The structure can be washed and disinfected.

WORKTOP

Worktop made of self-extinguishing ABS with raised edges on three sides. The worktop is resistant to scratches and stains and can be cleaned, washed and disinfected.

DRAWER UNIT

Drawers are made of powder-coated steel and run on telescopic **soft-closing** slides allowing their complete extraction. Drawers are provided with ergonomic and anti-trauma **aluminium** handles and stopper. Centralized key lock.

Standard drawer configuration:

1 drawer, ext. height 100 mm; 2 drawers, ext. height 150 mm; 2 drawers, ext. height 200 mm.

LEFT SIDE

Ergonomic and anti-trauma ABS push handle

BASE

Double shock absorbent bumper to prevent the trolley from turning over.

4 thermoformed swivel castors, Ø 125 mm, mounted on bearings; 2 are lockable.

Suggested configuration is equipped with the following accessories:

- Pull-up worktop;
- Knee-operated waste bin;

Overall dim.: 810x600x1100h mm