

STORM PLUS – PROCEDURE TROLLEY



Frame colours



Drawers colours



BEARING FRAME

Made by 4 powder-coated steel uprights that assure stability and consistency. Painting process complies with UNI EN ISO 9002 regulations.

SIDE AND REAR PANELS

Made of technopolymer with rounded edges. They are designed for the positioning of accessories. Load capacity: 100 kg

WORKTOP

Moulded technopolymer worktop with raised edges on three sides.

DRAWER UNIT

Removable and interchangeable drawers are made of powder-coated steel and run on **soft-closing** telescopic **slides** allowing their complete extraction. They are provided with ergonomic and anti-trauma **aluminium** handles and stopper. Centralized key lock.

Standard drawer configuration:

3 drawers, ext. height 150 mm; 1 drawer ext. height 300 mm

LEFT SIDE

Ergonomic and anti-trauma ABS push handle.

RIGHT SIDE

Technopolymer pull-out worktop.

BASE

Double perimetral and shock absorbent bumper to prevent the trolley from turning over. 4 thermoformed swivel castors, Ø 125 mm, mounted on bearings; 2 are lockable.

Suggested configuration is equipped with the following accessories:

- 3 tilt side storage compartments;

Overall dim.: 1100x650x1060 h mm