



aluminium handle

Frame colours



Charcoal grey



white

Drawers colours



green



blue



yellow



red



white

## STORM – PROCEDURE TROLLEY

### BEARING FRAME

Made by 4 powder-coated steel uprights that assure stability and consistency. Painting process complies with UNI EN ISO 9002 regulations.

### SIDE AND REAR PANELS

Made of technopolymer with rounded edges. They are designed for the positioning of accessories. Load capacity: 100 kg

### WORKTOP

Moulded technopolymer worktop with raised edges on three sides.

### DRAWER UNIT

Removable and interchangeable drawers are made of powder-coated steel and run on **soft-closing** telescopic **slides** allowing their complete extraction. They are provided with ergonomic and anti-trauma **aluminium** handles and stopper. Centralized key lock.

Standard drawer configuration:

1 drawer, ext. height 100 mm; 2 drawers, ext. height 150 mm; 1 drawer ext. height 250 mm

### LEFT SIDE

Ergonomic and anti-trauma ABS push handle.

### RIGHT SIDE

Technopolymer pull-out worktop.

### BASE

Double perimetral and shock absorbent bumper to prevent the trolley from turning over. 4 thermoformed swivel castors, Ø 125 mm, mounted on bearings; 2 are lockable.

Overall dim.: 750x650x1060 h mm