



SINO MEDICAL-DEVICE TECHNOLOGY CO., LTD.

6th floor, Building 15, No.1008 Songbai Road, Nanshan District, Shenzhen, P.R.China

Portable syringe pump SN-T1 / SN-T1R



Model No.		Syringe pump SN-T1 / SN-T1R
Features	Safety	Two sensors: Pressure sensor, Position sensor
	Performance & Function	Flow rate: 0.1mL/h-1800mL/h
		5ml, 10ml, 20ml, 30ml, 50ml/60ml
		Drug library
		2X9V battery, support 20hours at 5ml/h
		Open type, can calibrate every syringe
		PCA function
	Convenient	Suitable bag for pump
		Wireless
	Apperance	Portable: 500g only
Very small		
	Nice outlook	

Specification

Flow rate	0.1 ml/h~1800 ml/h
Accuracy of flow rate	±1.5%~±5%
Purge rate	5.0 ml/h~1800 ml/h
Volume delivered	0.1 mL~9999 mL
History	500pcs (can increase according to request)
Delivery limit	0.1 ml~9999 ml
KVO	0.1 ml~5.0 ml
Syringe	5ml, 10ml, 20ml, 30ml, 50/60ml
Syringe Specication	30 brands of syringe
Occlusion detection pressure	H,C,L
Alarm sound level	Adjustable---3 levels
Button sound	Adjustable---3 levels, can be on/off
Working mode	Speed mode, Time mode, Body weight mode, Infusion program
Other function	Drug library, PCA, Display of remained volume
Communication	Wireless with computer (SN-T1R)
Power	Support more than 20hours at the flow rate 5ml/h
Power supply	DC 12V
Battery	2X9V dry battery
Voltage	12VA
Working condisiton	Relative humidity: 20%~80%;
	Ambient temperature: +5℃~+40℃ ;
	Ambient pressure: 76kPa ~ 106kPa。
Weight (with clamp)	0.5 kg