

SN-600N/SN-600NR

Enteral Nutrition Pump

Transparent pump door,
visible infusion
process



Convenient

Transparent pump door;
The cam can be detached for
clean

Compact

Elegant streamline design,
weight only 1.3kg

Safe

Status light on top,
flow rate can be calibrated,
waterproof outlet

Intelligent

Bionic intermittent output,
wireless communication,
adjustable alarm sounds



Sino Medical-Device Technology Co., Ltd.
Build Quality, Build Reliability

SN-600N/SN-600NR Enteral Nutrition Pump

Specifications:

Items	parameter
Flow Rate	1 ml/h ~ 600 ml/h
Preset Volume	0 ml ~ 9999 ml
Display range of totally delivered volume	1 ml ~ 9999 ml
Accuracy	±5%
Bolus rate	3 levels: 200 ml/h, 400 ml/h, 600 ml/h (adjustable)
Automatic calibration	Automatic calibration: This unique design can adjust the flow accuracy automatically for nutrition solution with different viscosity
Occlusion accuracy	500±200mmHg
Alarm volume	3 levels
Keypad sound	Key tone can be set to mute, the volume has 3 levels
History recording	1500pcs
Communication with computer	Wireless communication (SN-600NR)
Power supply	AC 100V-240V, 50HZ / 60HZ
Inner battery	12V NiH 800mAh
Battery endurance	The device can work for more than 5 hours at the rate of 25ml/h after full charge. It takes 10 hours for fully charge with the device shut down
Power consumption	11 VA
Operation condition	Ambient Temperature: +5°C~+40°C relative humidity 20% ~ 90%, ambient pressure:76.0 kPa ~ 106.0kPa
Water proof level	IPX4
Dimension	146 mm (width)×199.5mm (height)×114mm (depth)
Weight	1.3kg (including the clamp base)
Electric shock protection class	Class I, type CF

Function :

DUAL-CPU monitoring function	USB connector	1500 history records
Adjust the flow accuracy by the way of volume calibration	Water proof design for the whole device	Wireless communication (SN-600NR)
Detection of dripping number	Abundant optic and sound alarm	Infusion status light can be on/off
Key lock function	The key tone can be set to mute	Infusion set flushing function
Power supply status	System time setting	Bionic intermittent output

Sino Medical-Device Technology Co., Ltd.

Add: 6th Floor, Building 15, No.1008, Songbai Road, Nanshan District, Shenzhen, P.R. China

Tel: +86 755 26755692 Fax: +86 755 26755687 Zip: 518055

Http://www.sinomdt.com Email: info@sinomdt.com

Franchiser:

Service hotline: 4008 860 121

V1.0