

## ALV900310 – PROCEDURE TROLLEY

### BODY

Structure made of powder-coated steel RAL 9006, thickness 10/10, finished with acrylic polyurethane enamels resistant to scratches, stains and corrosion. Painting process complies with UNI EN ISO 9002 regulations. The structure can be washed and disinfected.

### WORKTOP

Worktop made of self-extinguishing ABS mm with raised edges on three sides. It is resistant to scratches and stains and can be cleaned, washed and disinfected.

### DRAWER UNIT

Drawers are made of powder-coated steel and run on telescopic **soft-closing** slides allowing their complete extraction. They are provided with ergonomic and anti-trauma **aluminium** handles and stopper. Centralized key lock.

Standard drawer configuration:

- 1 drawer, ext. height 100 mm;
- 2 drawers, ext. height 150 mm;
- 2 drawers, ext. height 200 mm;

### LEFT SIDE

Technopolymer pull-out worktop with stopper.

### RIGHT SIDE

Ergonomic and anti-trauma ABS push handle

### BASE

Double shock absorbent bumper to prevent the trolley from turning over.  
4 thermoformed swivel castors, Ø 125 mm, mounted on bearings; 2 are lockable.

Overall dim.: 1100x640x1100h mm



aluminium handle

#### Drawers colours



green



blue



yellow



red



orange



sky blue



light green



white