

ALFA 01A – PROCEDURE TROLLEY

BODY

Structure made of powder-coated steel RAL 7035, thickness 10/10, finished with acrylic polyurethane enamels resistant to scratches, stains and corrosion. Painting process complies with UNI EN ISO 9002 regulations. The structure can be washed and disinfected.

WORKTOP

Worktop made of self-extinguishing ABS with raised edges on three sides. The worktop is resistant to scratches and stains and can be cleaned, washed and disinfected.

DRAWER UNIT

2 drawers, height 150 mm, made of powder-coated steel and run on telescopic **soft-closing slides** allowing their complete extraction. They are provided with ergonomic and anti-trauma **aluminium handles** and stopper.

Centralized key lock.

1 compartment with 1 inner shelf and 1 door made of powder-coated steel, height 500 mm (door key lock available upon request). Door is equipped with **aluminium handle**.

LEFT SIDE

Ergonomic and anti-trauma ABS push handle

BASE

Double perimetral and shock absorbent bumper to prevent the trolley from turning over. 4 thermoformed swivel castors, Ø 125 mm, mounted on bearings; 2 are lockable.

Suggested configuration is equipped with the following accessories:

- Pull-up worktop;
- Knee-operated waste bin;
- Medicine cup dispenser;

Overall dim.: 810x600x1100h mm



aluminium handle

Drawers colours



green



blue



yellow



red



white