

## ALFA 23 – PROCEDURE TROLLEY

### BODY

Structure made of powder-coated steel RAL 7035, thickness 10/10, finished with acrylic polyurethane enamels resistant to scratches, stains and corrosion. Painting process complies with UNI EN ISO 9002 regulations. The structure can be washed and disinfected.

### WORKTOP

Worktop made of self-extinguishing ABS with raised edges on three sides. The worktop is resistant to scratches and stains and can be cleaned, washed and disinfected.

### DRAWER UNIT

Drawers are made of powder-coated steel and run on **soft closing** telescopic slides allowing their complete extraction. They are provided with ergonomic and anti-trauma **aluminium handles** and stopper. Centralized key lock.

Standard drawer configuration:

2 drawers ext. height 100 mm; 4 drawers ext. height 150 mm; 4 drawers ext. height 200 mm;

### LEFT AND RIGHT SIDE

Ergonomic and anti-trauma ABS push handle.

### BASE

Double perimetral and shock absorbent bumper to prevent the trolley from turning over.

4 thermoformed swivel castors, Ø 125 mm, mounted on bearings;

2 are lockable, **1 is directional**.

***Suggested configuration is equipped with the following accessories:***

- Pull-up worktop;
- Knee-operated waste bin;
- Medicine cup dispenser;

Overall dim.: 1040 x 600 x 1110 h mm



aluminium handle

Drawers colours



green blue yellow red white